



## 6-Kt-Reduzier- Doppelnippel 417

EN 10241 / DIN 2990 Material AISI 316 Feinguss

Abmessung R-DIN 2999xR1	l mm	SW	Gew.kg/Stk
1/4"x 1/8"	27	15	0,02
3/8"x 1/4"	29	18	0,03
3/8"x 1/8"	29	18	0,03
1/2"x 3/8"	33	22	0,05
1/2"x 1/4"	33	22	0,05
1/2"x 1/8"	33	22	0,05
3/4"x 1/2"	37	28	0,08
3/4"x 3/8"	37	28	0,08
3/4"x 1/4"	37	28	0,08
3/4"x 1/8"	37	28	0,08
1"x 3/4"	42	35	0,18
1"x 1/2"	42	35	0,18
1"x 3/8"	42	35	0,17
1"x 1/4"	42	35	0,17
1 1/4"x 1"	47	43	0,20
1 1/4"x 3/4"	47	43	0,20
1 1/4"x 1/2"	47	43	0,19
1 1/4"x 3/8"	47	43	0,19
1 1/2"x 1 1/4"	50	50	0,26
1 1/2"x 1"	50	50	0,26
1 1/2"x 3/4"	50	50	0,25
1 1/2"x 1/2"	50	50	0,25
2"x 1 1/2"	55	62	0,42
2"x 1 1/4"	55	62	0,42
2"x 1"	55	62	0,40
2"x 3/4"	55	62	0,40
2" x 1/2"	55	62	0,40
2 1/2"x 2"	62	77	0,75
2 1/2"x 1 1/2"	62	77	0,75
2 1/2"x 1 1/4"	62	77	0,75
3"x 2 1/2"	71	91	0,95
3"x 2"	71	91	0,90
3"x 1 1/2"	71	91	0,90

