



G-Einschraubverschraubungen einstellbar

(Schaft mit S-DR und UE-M vormontiert) Einschraubgewinde: DIN/ISO 228
Whitworth-Rohrgewinde (zylindr.) Dichtkante Form B, DIN 3852 Teil 2
Auch mit Dichtkegel lieferbar.

Reihe	PN	Ra	G	i	d1	d3	S2	S1	I2	Gewicht %	Artikel	
L	250	6	G 1/8 A	8	M 12x1,5	14	14	14	24,5	2,3	CBL 6	
		8	G 1/4 A	12	M 14x1,5	18	17	19	29,5	5,2	CBL 8	
		10	G 1/4 A	12	M 16x1,5	18	19	19	27,5	4,8	CBL 10	
		12	G 3/8 A	12	M 18x1,5	22	22	22	34,0	8,6	CBL 12	
		15	G 1/2 A	14	M 22x1,5	26	27	27	32,0	11,9	CBL 15	
	160	18	G 1/2 A	14	M 26x1,5	26	32	27	31,5	13,3	CBL 18	
		22	G 3/4 A	16	M 30x2	32	36	32	32,5	18,7	CBL 22	
		100	28	G 1 A	18	M 36x2	39	41	41	35,0	26,6	CBL 28
			35	G 1 1/4 A	20	M 45x2	49	50	50	42,5	44,1	CBL 35
			42	G 1 1/2 A	22	M 52x2	55	60	55	46,5	63,4	CBL 42
S	630	6	G 1/4 A	12	M 14x1,5	18	17	19	27,0	4,5	CBS 6	
		8	G 1/4 A	12	M 16x1,5	18	19	19	29,5	5,6	CBS 8	
		10	G 3/8 A	12	M 18x1,5	22	22	22	32,0	8,4	CBS 10	
		12	G 3/8 A	12	M 20x1,5	22	24	22	34,0	9,6	CBS 12	
		14	G 1/2 A	14	M 22x1,5	26	27	27	36,5	14,7	CBS 14	
	400	16	G 1/2 A	14	M 24x1,5	26	30	27	37,0	15,8	CBS 16	
		20	G 3/4 A	16	M 30x2	32	36	32	43,0	25,6	CBS 20	
		25	G 1 A	18	M 36x2	39	46	41	48,0	49,9	CBS 25	
		250	30	G 1 1/4 A	20	M 42x2	49	50	50	51,0	66,6	CBS 30
			38	G 1 1/2 A	22	M 52x2	55	60	55	60,0	95,7	CBS 38

