



Einstellbare L-Anschlussverschraubungen

Schaft mit S-DR und UE-M vormontiert
Auch mit Dichtkegel lieferbar.

Reihe	PN	Ra	d1	S2	S1	I3	L2	I2	Gewicht %	Artikel	
L	250	6	M 12x1,5	14	12	26,0	29	14,0	6,3	FFL 6	
		8	M 14x1,5	17	12	27,5	29	14,0	8,1	FFL 8	
		10	M 16x1,5	19	14	29,0	30	15,0	10,1	FFL 10	
		12	M 18x1,5	22	17	29,5	32	17,0	13,1	FFL 12	
		15	M 22x1,5	27	19	32,5	36	21,0	22,4	FFL 15	
	160	18	M 26x1,5	32	24	35,5	40	23,5	33,1	FFL 18	
		22	M 30x2	36	27	39,5	44	27,5	47,8	FFL 22	
		100	28	M 36x2	41	36	41,5	47	30,5	60,4	FFL 28
			35	M 45x2	50	41	51,0	56	34,5	89,1	FFL 35
		42	M 52x2	60	50	56,0	63	40,0	132,6	FFL 42	
S	630	6	M 14x1,5	17	12	27,0	31	16,0	9,1	FFS 6	
		8	M 16x1,5	19	14	27,5	32	17,0	11,9	FFS 8	
		10	M 18x1,5	22	17	30,0	34	17,5	16,6	FFS 10	
		12	M 20x1,5	24	17	31,0	38	21,5	20,2	FFS 12	
		14	M 22x1,5	27	19	35,0	40	22,0	27,9	FFS 14	
	400	16	M 24x1,5	30	24	36,5	43	24,5	37,1	FFS 16	
		20	M 30x2	36	27	44,5	48	26,5	56,9	FFS 20	
		25	M 36x2	46	36	50,0	54	30,0	110,6	FFS 25	
		250	30	M 42x2	50	41	55,0	62	35,5	137,3	FFS 30
			38	M 52x2	60	50	63,0	72	41,0	195,0	FFS 38

