


## Winkel-Verschraubungen



Reihe	PN	Ra	S2	S1	L2	I2	Gewicht %	Artikel	
LL	100	4	10	9	21	11,0	1,9	<b>WV-04LL</b>	
		6	12	9	21	9,5	2,2	<b>WV-06LL</b>	
		8	14	12	23	11,5	3,1	<b>WV-08LL</b>	
L	250	6	14	12	27	12,0	4,2	<b>WV-06L</b>	
		8	17	12	29	14,0	5,9	<b>WV-08L</b>	
		10	19	14	30	15,0	7,4	<b>WV-10L</b>	
		12	22	17	32	17,0	9,9	<b>WV-12L</b>	
		15	27	19	36	21,0	16,4	<b>WV-15L</b>	
		160	18	32	24	40	23,5	24,8	<b>WV-18L</b>
		22	36	27	44	27,5	33,1	<b>WV-22L</b>	
		100	28	41	36	47	30,5	44,8	<b>WV-28L</b>
S	630	35	50	41	56	34,5	73,2	<b>WV-35L</b>	
		42	60	50	63	40,0	111,6	<b>WV-42L</b>	
		6	17	12	31	16,0	7,0	<b>WV-06S</b>	
		8	19	14	32	17,0	9,0	<b>WV-08S</b>	
		10	22	17	34	17,5	12,4	<b>WV-10S</b>	
		12	24	17	38	21,5	15,5	<b>WV-12S</b>	
		14	27	19	40	22,0	20,3	<b>WV-14S</b>	
		400	16	30	24	43	24,5	26,2	<b>WV-16S</b>
S	250	20	36	27	48	26,5	42,1	<b>WV-20S</b>	
		25	46	36	54	30,0	80,4	<b>WV-25S</b>	
		30	50	41	62	35,5	102,5	<b>WV-30S</b>	
		38	60	50	72	41,0	156,5	<b>WV-38S</b>	

