



LEGIERUNGSZUSCHLÄGE

FÜR ROST- UND SÄUREBESTÄNDIGE QUALITÄTEN

GÜLTIG AB 1. April 2019

Werkstoff Nr.	AISI	Rohr geschw. DIN 2463 Präzisionsbandstahl	Rohr nahtlos DIN 2462	Hohlstahl warmgefertigt	Bleche DIN 17440	Stabstahl gewalzt	Stabstahl blank
		EUR	EUR	EUR	EUR	EUR	EUR
1.4307	304	1,65	1,93	1,76	1,43	1,55	1,74
1.4306	304L	1,82	1,93	1,76	1,58	1,78	2,00
1.4404	316L	2,51	2,78	2,50	2,20	2,35	2,64
1.4435	316L	2,81	3,11	2,81	2,47	2,69	3,02
1.4436	316	2,79	-	-	2,40	2,59	2,90
1.4541	321	1,81	1,93	1,84	1,56	1,70	1,90
1.4571	316Ti	2,54	2,78	2,54	2,23	2,33	2,62
1.4462	Duplex	2,26	2,53	2,30	1,96	1,97	2,17
1.4539	904L	4,58	5,26	4,77	3,94	4,34	4,88

Werkstoff Nr.	Formstücke, Fittings, Flansche	Kugelhähne, Armaturen	Schneidringprogramm
1.4301/1.4541/304L	45%	0%	0%
1.4571/1.4436/316L	55%	0%	0%

