



LEGIERUNGSZUSCHLÄGE

FÜR ROST- UND SÄUREBESTÄNDIGE QUALITÄTEN

GÜLTIG AB 1. April 2021

| Werkstoff Nr. | AISI | Rohr geschw. DIN 2463 Präzisionsbandstahl | Rohr nahtlos DIN 2462 | Hohlstahl warmgefertigt | Bleche DIN 17440 | Stabstahl gewalzt | Stabstahl blank |
|---------------|--------|--|--------------------------|----------------------------|------------------|----------------------|-----------------|
| | | EUR | EUR | EUR | EUR | EUR | EUR |
| 1.4307 | 304 | 2,13 | 2,78 | 2,49 | 1,86 | 1,94 | 2,18 |
| 1.4306 | 304L | 2,35 | 2,78 | 2,53 | 2,07 | 2,26 | 2,53 |
| 1.4404 | 316L | 3,05 | 3,62 | 3,25 | 2,66 | 2,81 | 3,16 |
| 1.4435 | 316L | 3,40 | 3,67 | 4,12 | - | 3,20 | 3,59 |
| 1.4436 | 316 | - | - | - | - | 3,06 | 3,44 |
| 1.4541 | 321 | 2,33 | 2,78 | 2,58 | 2,03 | 2,17 | 2,43 |
| 1.4571 | 316Ti | 3,10 | 3,62 | 3,25 | 2,70 | 2,81 | 3,16 |
| 1.4462 | Duplex | 2,58 | 2,73 | 2,72 | 2,25 | 2,15 | 2,41 |
| 1.4539 | 904L | 5,43 | 6,62 | 6,49 | - | 5,24 | 5,89 |

| Werkstoff Nr. | Formstücke, Fittings, Flansche | Kugelhähne, Armaturen | Schneidringprogramm |
|--------------------|--------------------------------|-----------------------|---------------------|
| 1.4301/1.4541/304L | 61 % | 0% | 0% |
| 1.4571/1.4436/316L | 67 % | 0% | 0% |

