



Verschraubung S/AG 426 A konisch dichtend
Verschraubung S/AG 428 A flach dichtend

EN 10241 Schweißenden/Außengewinde, Material AISI 316 Feinguss

| Abmessung Rp-DIN 2999 | D mm | L mm | W mm | SW | Gew.kg/Stk. |
|-----------------------|-------|------|------|-----|-------------|
| 1/8" | 10,2 | 42 | 12 | 27 | 0,09 |
| 1/4" | 13,5 | 42 | 12 | 27 | 0,09 |
| 3/8" | 17,2 | 45 | 13 | 31 | 0,11 |
| 1/2" | 21,3 | 53 | 14 | 38 | 0,16 |
| 3/4" | 26,9 | 57 | 14 | 45 | 0,22 |
| 1" | 33,7 | 68 | 17 | 54 | 0,35 |
| 1 1/4" | 42,4 | 71 | 17 | 64 | 0,47 |
| 1 1/2" | 48,3 | 79 | 19 | 72 | 1,58 |
| 2" | 60,3 | 88 | 21 | 86 | 1,04 |
| 2 1/2" | 76,1 | 98 | 23 | 105 | 1,53 |
| 3" | 88,9 | 108 | 26 | 122 | 2,21 |
| 4" | 114,3 | 123 | 30 | 150 | 2,95 |

