




Rohrkappen DIN 28011

Aus Blech gepresst und gebeizt.
Kurzfristig lieferbar im Werkstoff 1.4307 und 1.4404/1.4571
Auf Wunsch mit Abnahmeprüfzeugnis EN 10204/3.1



Abmessungen d1 x s	Bauhöhe L	Gew. kg
Iso-Abmessungen		
21,3 x 2,0	9,0	0,01
26,9 x 2,0	9,0	0,01
33,7 x 2,0	13,0	0,02
42,4 x 2,0	13,0	0,04
48,3 x 2,0	13,5	0,05
60,3 x 2,0	18,5	0,07
76,1 x 2,0	20,5	0,10
88,9 x 2,0	25,0	0,15
114,3 x 2,0	28,0	0,26
114,3 x 3,0	29,0	0,39
139,7 x 3,0	38,5	0,60
168,3 x 3,0	47,5	0,90
219,1 x 3,0	63,5	1,32
273,0 x 3,0	93,0	1,95
323,9 x 3,0	102,0	2,70
355,6 x 3,0	109,0	3,80
406,4 x 3,0	123,0	5,00
457,2 x 3,0	123,0	6,10
508,0 x 3,0	133,0	7,60

Abmessungen d x s	Bauhöhe h(ca.)	Gew. kg
Metrische Abmessungen		
20,0 x 2,0	9,0	0,02
25,0 x 2,0	9,0	0,03
30,0 x 2,0	13,5	0,03
35,0 x 2,0	13,5	0,04
44,0 x 2,0	15,0	0,04
54,0 x 2,0	15,0	0,05
70,0 x 2,0	19,5	0,07
84,0 x 2,0	24,0	0,15
104,0 x 2,0	28,0	0,2
129,0 x 2,0	37,0	0,36
154,0 x 2,0	43,0	0,5
156,0 x 3,0	44,0	0,94
204,0 x 2,0	62,0	0,8
206,0 x 3,0	63,0	1,2
254,0 x 2,0	72,0	1,3
256,0 x 3,0	73,0	1,95
306,0 x 3,0	83,0	2,5

Liefermöglichkeiten für weitere Abmessungen, Werkstoffe, sowie für reduzierte Sattelstützen auf Anfrage.

