



Einstellbare Winkel-Anschlussverschraubungen

Mit geraden Einschraubstützen DIN 13
Auch mit Dichtkegel lieferbar.

Reihe	PN	Ra	G	i	d3	S2	S1	S3	I3	L2	I2	Gewicht %	Artikel	
L	250	6	M 10x1	8	14	14	12	14	35,0	29	14,0	5,7	EVW-06LM 10x1,0	
		8	M 12x1,5	12	17	17	12	17	37,5	29	14,0	8,2	EVW-08LM 12x1,5	
		10	M 14x1,5	12	19	19	14	19	40,0	30	15,0	9,6	EVW-10LM 14x1,5	
		12	M 16x1,5	12	21	22	17	22	42,0	32	17,0	13,4	EVW-12LM 16x1,5	
		15	M 18x1,5	12	23	27	19	24	46,0	36	21,0	22,9	EVW-15LM 18x1,5	
	160	18	M 22x1,5	14	27	32	24	27	50,0	40	23,5	30,5	EVW-18LM 22x1,5	
		22	M 26x1,5	16	31	36	27	32	55,0	44	27,5	41,5	EVW-22LM 26x1,5	
		100	28	M 33x2	18	39	41	36	41	59,0	47	30,5	61,4	EVW-28LM 33x2,0
			35	M 42x2	20	49	50	41	50	69,0	56	34,5	98,5	EVW-35LM 42x2,0
			42	M 48x2	22	55	60	50	55	75,0	63	40,0	141,7	EVW-42LM 48x2,0
S	630	6	M 12x1,5	12	17	17	12	17	40,0	31	16,0	9,9	EVW-06SM 12x1,5	
		8	M 14x1,5	12	19	19	14	19	43,0	32	17,0	12,1	EVW-08SM 14x1,5	
		10	M 16x1,5	12	21	22	17	22	45,0	34	17,5	16,9	EVW-10SM 16x1,5	
		12	M 18x1,5	12	23	24	17	24	48,0	38	21,5	20,2	EVW-12SM 18x1,5	
		14	M 20x1,5	14	25	27	19	27	54,0	40	22,0	28,7	EVW-14SM 20x1,5	
	400	16	M 22x1,5	14	27	30	24	27	54,0	43	24,5	33,9	EVW-16SM 22x1,5	
		20	M 27x2	16	32	36	27	32	65,0	48	26,5	55,1	EVW-20SM 27x2,0	
		25	M 33x2	18	39	46	36	41	79,0	54	30,0	105,4	EVW-25SM 33x2,0	
		250	30	M 42x2	20	49	50	41	50	79,0	62	35,5	139,8	EVW-30SM 42x2,0
			38	M 48x2	22	55	60	50	55	89,0	72	41,0	194,4	EVW-38SM 48x2,0

